Externally Relieved Body Screw - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5305-01-144-1486

hread Direction: ight-hand hread Length: .138 inches astener Length: .530 inches lead Style: lat countersunk undercut lead Diameter: .279 inches lead Height: .047 inches lead Height: .048 inches lead Height: .049 inches lead Height: .040 inches hread Diameter: .200 inches hread Qty Per Inch (tpi): .2 countersink Angle: .00.0 degrees ixternally Relieved Body Diameter Quantity: Haterial: tainless steel straface Treatment:	
hread Length:   .138 inches   astener Length:   .530 inches   lead Style:   .530 inches   lead Style:   lat countersunk undercut   lead Diameter:   .279 inches   lead Height:   .047 inches   irst Diameter From Head:   .095 inches   vistance From Largest Bearing Surface Of Head To End Of First Diameter:   .283 inches   vistance From Largest Bearing Surface Of Head To End Of First Diameter:   .283 inches   vistance Style:   .006   hread Diameter:   .200 inches   hread Diameter:   .210 inches   .221 inches   .222 inches   .232 inches	
138 inches astener Length: .530 inches Lead Style: lat countersunk undercut lead Diameter: .279 inches Lead Height: .047 inches Iterad Height: .047 inches Iterad Iteratise Iter	
astener Length: .530 inches Lead Style: lat countersunk undercut Lead Diameter: .279 inches Lead Height: .279 inches Lead Height: .047 inches Lead Height: .047 inches Lead Height: .047 inches Lead Height: .047 inches Lead Height: .047 inches Lead Height: .047 inches Lead Height: .049 inches Lead Height: .040 inches Lead Height: .200 inches Lead Diameter: .200 inches .200 inches .20	
530 inches lead Style: lat countersunk undercut lead Diameter: .279 inches lead Height: .279 inches lead Height: .047 inches listed Height: .047 inches listed Trom Head: .095 inches listence From Largest Bearing Surface Of Head To End Of First Diameter: .283 inches listence Style: .283 inches listence Diameter: .200 inches listence Diameter: .200 inches listence Inch (tpi): .2 sountersink Angle: .00.0 degrees listernally Relieved Body Diameter Quantity: listence Inches list	
lead Style: lat countersunk undercut lead Diameter: .279 inches lead Height: .279 inches lead Height: .047 inches lead Height: .047 inches lead Height: .047 inches list Diameter From Head: .095 inches list notee From Largest Bearing Surface Of Head To End Of First Diameter: .283 inches list notee Style: .283 inches lead Diameter: .200 inches listeraal Diameter: .200 inches listeraal Vity Per Inch (tpi): .2 Sountersink Angle: .0.0 degrees kternally Relieved Body Diameter Quantity: Haterial: tainless steel	
lat countersunk undercut lead Diameter: .279 inches lead Height:279 inches lead Height:	
lead Diameter: .279 inches lead Height: .047 inches inst Diameter From Head: .095 inches bistance From Largest Bearing Surface Of Head To End Of First Diameter: .283 inches .283 inches .283 inches .200 inches hread Diameter: .200 inches hready Qty Per Inch (tpi): .2 countersink Angle: .0.0 degrees citernally Relieved Body Diameter Quantity: Material: trainless steel	
279 inches lead Height:	
lead Height: .047 inches iirst Diameter From Head: .095 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: .283 inches .283 inches hternal Drive Style: .300 inches hread Diameter: .200 inches hready Qty Per Inch (tpi): 2 Sountersink Angle: .00.0 degrees Externally Relieved Body Diameter Quantity: Haterial: trainless steel	
.047 inches irst Diameter From Head: .095 inches istance From Largest Bearing Surface Of Head To End Of First Diameter: .283 inches iternal Drive Style: .283 inches iternal Drive Style: .200 inches .200 inches hready Qty Per Inch (tpi): .2 countersink Angle: .0.0 degrees ixternally Relieved Body Diameter Quantity: Iternally Relieved Body Diameter Quantity:	
irst Diameter From Head: .095 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: .283 inches hternal Drive Style: .204 hread Diameter: .200 inches hready Qty Per Inch (tpi): 2 Sountersink Angle: .00.0 degrees Externally Relieved Body Diameter Quantity: Haterial: Etainless steel	
.095 inches   Distance From Largest Bearing Surface Of Head To End Of First Diameter:   .283 inches   Internal Drive Style:   alot   Interad Diameter:   .200 inches   Interady Qty Per Inch (tpi):   2   Sountersink Angle:   00.0 degrees   Externally Relieved Body Diameter Quantity:	
Anternal Drive Style: .283 inches hternal Drive Style: .300 inches hready Qty Per Inch (tpi): 2 countersink Angle: 00.0 degrees ixternally Relieved Body Diameter Quantity: Material: itainless steel	
.283 inches internal Drive Style: idot ihread Diameter: .200 inches ihready Qty Per Inch (tpi): 2 countersink Angle: 00.0 degrees ixternally Relieved Body Diameter Quantity: Itaterial: itainless steel	
hternal Drive Style: dot hread Diameter: .200 inches hready Qty Per Inch (tpi): 2 countersink Angle: 00.0 degrees ixternally Relieved Body Diameter Quantity: hterial: itainless steel	
Not Shot Shot Shread Diameter: .200 inches Phready Qty Per Inch (tpi): 2 Sountersink Angle: 00.0 degrees Externally Relieved Body Diameter Quantity: Naterial:	
Thread Diameter:   .200 inches   Thready Qty Per Inch (tpi):   2   Countersink Angle:   00.0 degrees   Externally Relieved Body Diameter Quantity:	
200 inches hready Qty Per Inch (tpi): 2 countersink Angle: 00.0 degrees xternally Relieved Body Diameter Quantity: Naterial: bitainless steel	
Thready Qty Per Inch (tpi): 2 Countersink Angle: 00.0 degrees Externally Relieved Body Diameter Quantity: Naterial:	
2 countersink Angle: 00.0 degrees ixternally Relieved Body Diameter Quantity: laterial: itainless steel	
Countersink Angle: 00.0 degrees Externally Relieved Body Diameter Quantity: Naterial:	
00.0 degrees Externally Relieved Body Diameter Quantity: Naterial: Stainless steel	
Externally Relieved Body Diameter Quantity: Iaterial: Stainless steel	
laterial: itainless steel	
laterial: itainless steel	
tainless steel	
lassivate	
hread Series Designator:	
chelf Life:	
I/a	
Init Of Measure:	
Demilitarization:	
iig:	
.003b0	