NSN 5305-01-144-6258

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-144-6258 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 0.240 inches and 0.250 inches **Fastener Length:** Between 0.859 inches and 0.891 inches **Head Style:** Knurled no. 4 **Head Diameter:** Between 0.370 inches and 0.380 inches **Head Height:** Between 0.422 inches and 0.454 inches **First Diameter From Head:** Between 0.125 inches and 0.135 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.453 inches and 0.485 inches **Internal Drive Style:** Slot **Thread Diameter:** 0.190 inches Thready Qty Per Inch (tpi): **Externally Relieved Body Diameter Quantity:** 1 Material: Steel comp 303 or steel comp 303se **Material Specification:** Astma582 assn standard single material response **Surface Treatment: Passivate Surface Treatment Specification:** Qq-p-35 federal specification single treatment response **Thread Series Designator:** Unf Shelf Life: N/a **Unit Of Measure: Demilitarization:**

No

NSN 5305-01-144-6258

Externally Relieved Body Screw - Page 2 of 2



Fiig:

A003b0