## NSN 5305-01-144-6268



Setscrew - Page 1 of 1 View Online at https://aerobasegroup.com/nsn/5305-01-144-6268 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 0.240 inches and 0.260 inches **Fastener Length:** Between 0.240 inches and 0.260 inches **Head Style:** Headless (setscrew) Point Style: Flat **Internal Drive Style:** Hexagon **Thread Diameter:** 0.250 inches Width Across Flats: 0.125 inches Thready Qty Per Inch (tpi): 28 **Criticality Code Justification:** Zzzy Material: Steel comp 302 or steel comp 302b or steel comp 303 or steel comp 303 plus x or steel comp 303se or steel comp 303cu or steel comp 303pb **Special Test Features:** Special quality control testing **Test Data Document:** 81349-mil-p-23199 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). **Thread Series Designator:** Unf **Reference Number Differentiating Characteristics:** As differentiated by material which must conform to ships parts control center special quality control provisions and certified free from mercury contamination Shelf Life: N/a **Unit Of Measure: Demilitarization:** 

Fiig: A003b0

No