NSN 5305-01-144-7379

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-144-7379 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: 0.380 inches **Fastener Length:** 1.750 inches **Head Style:** Knurled no. 4 **Head Diameter:** 0.620 inches **Head Height:** 0.250 inches **First Diameter From Head:** 0.180 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: 1.370 inches **Internal Drive Style:** Slot **Thread Diameter:** 0.250 inches Thready Qty Per Inch (tpi): 20 **Externally Relieved Body Diameter Quantity:** 1 **Special Features:** Medium straight knurl Material: Steel comp 303 **Material Specification:** Qq-s-763 federal specification single material response **Surface Treatment:** Cadmium and chromate **Surface Treatment Specification:** Mil-f-14072 military specification single treatment response **Thread Series Designator:** Unc Shelf Life: N/a **Unit Of Measure:**

--

NSN 5305-01-144-7379

Externally Relieved Body Screw - Page 2 of 2



_						
11	em)	 tor	172	+ 1	nn	

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-f-14072 spec.