NSN 5305-01-145-1191

Machine Screw - Page 1 of 2

3a

28

View Online at https://aerobasegroup.com/nsn/5305-01-145-1191



Thread Class: Thread Direction: Right-hand Thread Length: 0.506 inches **Fastener Length:** Between 0.704 inches and 0.750 inches **Head Style:** Pan **Head Diameter:** Between 0.473 inches and 0.492 inches **Head Height:** Between 0.162 inches and 0.175 inches Locking Feature: Patch **Internal Drive Style:** Cross recess type iii **Thread Diameter:** 0.250 inches Thready Qty Per Inch (tpi): Hardness Rating: Between 26.0 rockwell c and 32.0 rockwell c **Screw Material:** Steel comp 4340 or steel comp 8740 Locking Feature Material: Plastic polyamide **Screw Material Specification:** Mil-s-5000 military specification 1st material response or ams 6322 assn standard single material response Locking Feature Material Specification: Milf-18240 military specification single material response **Screw Surface Treatment:** Cadmium and chromate **Screw Surface Treatment Specification:** Qq-p-416, type 2, class 3 federal specification all treatment responses **Thread Series Designator:** Unf Shelf Life: N/a Unit Of Measure:

NSN 5305-01-145-1191

Machine Screw - Page 2 of 2

Demilitarization:

No

Fiig:

A500d0

Mil-std (military Standard):

spec.

