Externally Relieved Body Screw - Page 1 of 2



or steel comp 316l or steel

View Online at https://aerobasegroup.com/nsn/5305-01-145-5440

Thread Class	
2a	
Thread Direct	ion:
Right-hand	
Thread Lengt	h:
0.144 inches	
Fastener Len	gth:
0.380 inches	
Head Style:	
Flat countersu	nk
Head Diamete	er:
0.172 inches	
First Diamete	r From Head:
0.060 inches	
Distance From	n Largest Bearing Surface Of Head To End Of First Diameter:
0.200 inches	
Internal Drive	Style:
Cross recess t	ype 1
Thread Diame	ster:
0.086 inches	
Thready Qty I	Per Inch (tpi):
56	
Countersink /	Angle:
82.0 degrees	
Externally Re	lieved Body Diameter Quantity:
1	
Material:	
Steel comp 30	2 or steel comp 304 or steel comp 304l or steel comp 305 or steel comp 310 or steel comp 316
comp 317 or s	steel comp 321 or steel comp 347 or steel comp 309
Material Spec	ification:
66 federal star	idard all material responses
Surface Treat	ment:
Passivate	
Surface Treat	ment Specification:
Qq-p-35 feder	al specification single treatment response
Thread Series	Designator:
Unc	
Shelf Life:	
N/a	
Unit Of Measu	ıre:
Demilitarizati	on:
No	

## NSN 5305-01-145-5440

Externally Relieved Body Screw - Page 2 of 2

Fiig: A003b0

