Socket Head Cap Screw - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5305-01-145-7979



Thread Class: 3a **Thread Direction: Right-hand Thread Length:** Between 0.283 inches and 0.375 inches Fastener Length: Between 0.345 inches and 0.375 inches **Head Style:** Flat chamfer **Head Diameter:** Between 0.218 inches and 0.226 inches **Head Height:** Between 0.134 inches and 0.138 inches Hole Diameter: Between 0.033 inches and 0.039 inches **Internal Drive Style:** Hexagon **Thread Diameter:** 0.138 inches Width Across Flats: Between 0.109 inches and 0.111 inches Hole Quantity: Hole Type: Drilled Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 160000 pounds per square inch Hole Configuration Style: Round internal hexagon Material: Iron alloy 660 **Material Specification:** Ams 5731 assn standard single material response or ams 5737 assn standard single material response **Surface Treatment:** Passivate **Surface Treatment Specification:** Qq-p-35 federal specification single treatment response **Thread Series Designator:**

Unrc

2

NSN 5305-01-145-7979

Socket Head Cap Screw - Page 2 of 2



Specification Data:

80205-nas1352 professional/industrial association standard

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A003b0