

View Online at <https://aerobasegroup.com/nsn/5305-01-145-8394>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.997 inches and 1.029 inches

**Fastener Length:**

Between 2.701 inches and 2.717 inches

**Head Style:**

Crowned hexagon

**Head Height:**

Between 0.376 inches and 0.391 inches

**Width Between Flats:**

Between 1.052 inches and 1.064 inches

**Locking Feature:**

Detent ball grip

**Grip Diameter:**

Between 0.7486 inches and 0.7491 inches

**Shank Unthreaded Hole Diameter:**

0.141 inches first hole and 0.151 inches first hole

**Internal Drive Style:**

Slot

**Thread Diameter:**

0.750 inches

**Grip Length:**

Between 1.688 inches and 1.704 inches

**Thready Qty Per Inch (tpi):**

16

**Min. Tensile Strength (psi):**

170000 pounds per square inch

**Hardness Rating:**

38.0 rockwell c fastener and 45.0 rockwell c fastener

**Distance From Head Largest Bearing Surface To Shank Hole Center:**

2.503 inches first hole and 2.519 inches first hole

**Surface Finish:**

32.0 microinches grip

**Material:**

Steel comp 631 spring or steel comp 302 spring

**Material Specification:**

Ams5678 assn standard 1st material response spring or astm a580 cond. A assn standard 2nd material response spring

**Surface Treatment:**

Passivate spring

**Surface Treatment Specification:**

Qq-p-35 federal specification single treatment response spring

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0