## NSN 5305-01-146-0523

Shoulder Screw - Page 1 of 2

3a

24

Unjf

N/a

View Online at https://aerobasegroup.com/nsn/5305-01-146-0523



## **Thread Class: Thread Direction: Right-hand Thread Length:** Between 0.350 inches and 0.400 inches Fastener Length: Between 1.172 inches and 1.202 inches **Head Style:** Flat countersunk **Head Diameter:** Between 0.625 inches and 0.635 inches Shoulder Diameter: 0.3271 inches first shoulder and 0.3276 inches first shoulder Shoulder Length: 0.676 inches first shoulder and 0.696 inches first shoulder Shank Unthreaded Hole Diameter: 0.076 inches first hole and 0.081 inches first hole **Internal Drive Style:** High-torque **Thread Diameter:** 0.312 inches Thready Qty Per Inch (tpi): **Countersink Angle:** Between 99.0 degrees and 101.0 degrees Distance From Head Largest Bearing Surface To Shank Hole Center: 1.049 inches first hole and 1.089 inches first hole Shoulder Shape: Round first shoulder Material: Steel comp xm-13 **Material Specification:** Ams5629 assn standard single material response Surface Treatment: Passivate **Surface Treatment Specification:** Qq-p-35 federal specification single treatment response **Thread Series Designator:** Shelf Life:

## NSN 5305-01-146-0523

Shoulder Screw - Page 2 of 2

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A003b0

