NSN 5305-01-146-0524

Shoulder Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-146-0524 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.630 inches and 0.697 inches **Fastener Length:** Between 1.890 inches and 1.937 inches **Head Style:** Flat countersunk undercut **Head Diameter:** Between 0.881 inches and 0.888 inches **Head Height:** Between 0.124 inches and 0.127 inches **Shoulder Diameter:** 0.4521 inches first shoulder and 0.4526 inches first shoulder **Shoulder Length:** 1.113 inches first shoulder and 1.136 inches first shoulder **Internal Drive Style:** High-torque **End Application:** F414 engine (f/a-18 f&g aircraft)aircraft hornet f/a-18 **Thread Diameter:** 0.438 inches Thready Qty Per Inch (tpi): 20 **Countersink Angle:** Between 99.0 degrees and 101.0 degrees **Shoulder Shape:** Round first shoulder **Special Features:** Furnished with one rubber o ring Material: Steel comp xm-13 **Material Specification:** Ams5629 assn standard single material response **Thread Series Designator:** Unjf Shelf Life: N/a **Unit Of Measure:**

--

NSN 5305-01-146-0524

Shoulder Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0