## NSN 5305-01-146-1723

Shoulder Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-146-1723 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.366 inches and 0.416 inches **Fastener Length:** Between 1.251 inches and 1.281 inches **Head Style:** Flat countersunk **Head Diameter:** Between 0.752 inches and 0.762 inches **Shoulder Diameter:** 0.3896 inches first shoulder and 0.3901 inches first shoulder **Shoulder Length:** 0.712 inches first shoulder and 0.732 inches first shoulder **Internal Drive Style:** High-torque **Thread Diameter:** 0.375 inches Thready Qty Per Inch (tpi): 24 **Countersink Angle:** Between 99.0 degrees and 101.0 degrees **Shoulder Shape:** Round first shoulder Material: Steel comp xm-13 **Material Specification:** Ams5629 assn standard single material response **Surface Treatment: Passivate Surface Treatment Specification:** Qq-p-35 federal specification single treatment response **Thread Series Designator:** Unjf Shelf Life: N/a **Unit Of Measure:** 

**Demilitarization:** 

No

## NSN 5305-01-146-1723

Shoulder Screw - Page 2 of 2



Fiig:

A003b0