

View Online at <https://aerobasegroup.com/nsn/5305-01-146-6130>

Thread Class:

2a

Thread Direction:

Right-hand

Thread Length:

Between 0.320 inches and 0.375 inches

Fastener Length:

Between 0.345 inches and 0.375 inches

Head Style:

Flat countersunk

Head Diameter:

Between 0.099 inches and 0.119 inches

Internal Drive Style:

Cross recess type 1

Thread Diameter:

0.060 inches

Thready Qty Per Inch (tpi):

80

Min. Tensile Strength (psi):

80000 pounds per square inch

Countersink Angle:

Between 80.0 degrees and 82.0 degrees

Screw Material:

Steel comp 302 or steel comp 304 or steel comp 304l or steel comp 305 or steel comp 309 or steel comp 310 or steel comp 316 or steel comp 316l or steel comp 317 or steel comp 321 or steel comp 347

Screw Material Specification:

66 federal standard all material responses

Screw Surface Treatment:

Oxide

Screw Surface Treatment Specification:

Mil-c-13924, class 4 military specification single treatment response

Color:

Black

Thread Series Designator:

Unf

Specification Or Standard:

3 type and 2c style

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A500d0

Mil-std (military Standard):

Mil-c-13924 spec.