NSN 5305-01-146-9765

Socket Head Cap Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-146-9765 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.470 inches and 0.562 inches **Fastener Length:** Between 0.532 inches and 0.562 inches **Head Style:** Flat chamfer **Head Diameter:** Between 0.218 inches and 0.226 inches **Head Height:** Between 0.134 inches and 0.138 inches **Hole Diameter:** Between 0.033 inches and 0.039 inches **Internal Drive Style:** Hexagon **Thread Diameter:** 0.138 inches Width Across Flats: Between 0.1094 inches and 0.1111 inches **Hole Quantity:** 2 **Hole Type:** Drilled Thready Qty Per Inch (tpi): Min. Tensile Strength (psi): 160000 pounds per square inch **Hole Configuration Style:** Round internal hexagon Material: Iron alloy 660 **Material Specification:** Ams5731 assn standard single material response or ams5737 assn standard single material response **Surface Treatment: Passivate Surface Treatment Specification:**

Unrc

Thread Series Designator:

Qq-p-35 federal specification single treatment response

NSN 5305-01-146-9765

Socket Head Cap Screw - Page 2 of 2



Specification Data	Spe	ecifica	ition	Data:
--------------------	-----	---------	-------	-------

80205-nas1352 professional/industrial association standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0