Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-147-4880

hread Class:	
а	
hread Direction:	
Right-hand	
hread Length:	
.109 inches	
astener Length:	
.266 inches	
lead Style:	
lat chamfer	
lead Diameter:	
.188 inches	
lead Height:	
.050 inches	
irst Diameter From Head:	
etween 0.120 inches and 0.123 inches	
Second Diameter From Head:	
Between 0.058 inches and 0.063 inches	
Distance From Largest Bearing Surface Of Head To End Of First I	Diameter:
Between 0.112 inches and 0.117 inches	
Distance From Largest Bearing Surface Of Head To End Of Secor	nd Diameter:
.157 inches	
nternal Drive Style:	
Slot	
hread Diameter:	
.086 inches	
hready Qty Per Inch (tpi):	
6	
externally Relieved Body Diameter Quantity:	
laterial:	
stainless steel	
Surface Treatment:	
Passivate	
Surface Treatment Specification:	
Qq-p-35 federal specification single treatment response	
hread Series Designator:	
Inc	
shelf Life:	
I/a	
Init Of Measure:	

NSN 5305-01-147-4880

Externally Relieved Body Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0