Socket Head Cap Screw - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5305-01-147-4891



Thread Class: 3a **Thread Direction: Right-hand Thread Length:** Between 0.512 inches and 0.625 inches Fastener Length: Between 0.595 inches and 0.625 inches **Head Style:** Flat chamfer **Head Diameter:** Between 0.303 inches and 0.312 inches **Head Height:** Between 0.185 inches and 0.190 inches **Internal Drive Style:** Hexagon **Thread Diameter:** 0.190 inches Width Across Flats: 0.156 inches Thready Qty Per Inch (tpi): 24 Min. Tensile Strength (psi): 180000 pounds per square inch Hardness Rating: 39.0 rockwell c and 45.0 rockwell c **Minimum Yield Strength:** 155000 pounds per square inch Material: Steel **Material Specification:** Astm a574 assn standard all material responses Surface Treatment: Zinc and chromate Surface Treatment Specification: Astm b633, type 2, class fe/zn5 assn standard all treatment responses **Thread Series Designator:** Unc **Specification Or Standard:** 6 type Shelf Life: N/a

NSN 5305-01-147-4891

Socket Head Cap Screw - Page 2 of 2

Unit Of Measure:

Demilitarization:

No

Fiig:

A003b0

