NSN 5305-01-147-6734

Socket Head Cap Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-147-6734 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 0.158 inches and 0.250 inches **Fastener Length:** Between 0.220 inches and 0.250 inches **Head Style:** Flat chamfer **Head Diameter:** Between 0.218 inches and 0.226 inches **Head Height:** Between 0.134 inches and 0.138 inches **Hole Diameter:** 0.046 inches **Internal Drive Style:** Hexagon **Thread Diameter:** 0.138 inches Width Across Flats: 0.109 inches **Hole Quantity: Hole Type:** Drilled Thready Qty Per Inch (tpi): **Hole Configuration Style:** Round internal hexagon **Criticality Code Justification:** Zzzy

,

Material:

Steel comp 302 or steel comp 302b or steel comp 303 or steel comp 303se or steel comp 303cu or steel comp 303pb or steel comp 303 plus x or steel comp 303ma or steel comp 304 or steel comp 304l

Material Specification:

Aisi assn standard all material responses

Surface Treatment:

Chromium

Special Test Features:

Special quality control testing

Surface Treatment Specification:

Qq-c-320, cl 2b federal specification single treatment response

NSN 5305-01-147-6734

Socket Head Cap Screw - Page 2 of 2



Test Data Document:

81349-mil-p-23199 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Thread Series Designator:

Unc

Reference Number Differentiating Characteristics:

As differentiated by material which must conform to ships parts control center special quality control provisions and certified free from mercury contamination

Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:

A003b0