NSN 5305-01-147-6736

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-147-6736 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.287 inches and 0.337 inches **Fastener Length:** Between 0.609 inches and 0.639 inches **Head Style:** Oval countersunk **Head Diameter:** Between 0.297 inches and 0.302 inches **Grip Diameter:** Between 0.1885 inches and 0.1895 inches **Internal Drive Style:** High-torque **Thread Diameter:** 0.190 inches **Grip Length:** Between 0.302 inches and 0.322 inches Thready Qty Per Inch (tpi): 32 **Countersink Angle:** Between 99.0 degrees and 101.0 degrees Material: Steel comp xm-13 **Material Specification:** Ams5629 assn standard single material response **Surface Treatment:** Aluminum and chromate **Surface Treatment Specification:** Mil-c-83488, type 2, cl 3 military specification single treatment response **Thread Series Designator:** Unjf Shelf Life: N/a **Unit Of Measure: Demilitarization:**

No Fiig:

A003b0

NSN 5305-01-147-6736

Close Tolerance Screw - Page 2 of 2



Mil-std (military Standard):

Mil-c-83488 spec.