Socket Head Cap Screw - Page 1 of 2



| Socket Head Cap Screw - Page 1 of 2 |
|---|
| View Online at https://aerobasegroup.com/nsn/5305-01-147-8314 |
| Thread Class: |
| 3a |
| Thread Direction: |
| Right-hand |
| Thread Length: |
| 0.375 inches |
| Fastener Length: |
| 0.375 inches |
| Head Style: |
| Flat chamfer |
| Head Diameter: |
| 0.312 inches |
| Head Height: |
| 0.190 inches |
| Hole Diameter: |
| 0.046 inches |
| Internal Drive Style: |
| Hexagon |
| Thread Diameter: |
| 0.190 inches |
| Width Across Flats: |
| 0.156 inches |
| Hole Quantity: |
| |
| |
| Drilled |
| Thready Qty Per Inch (tpi): |
| 32 Min Toncilo Strongth (noi) |
| Min. Tensile Strength (psi): 200000 pounds per square inch |
| Hardness Rating: |
| 34.0 rockwell c and 40.0 rockwell c |
| Hole Configuration Style: |
| Round internal hexagon |
| Criticality Code Justification: |
| Cqbc |
| Material: |
| Steel comp 4037 |
| Material Specification: |
| Ams 6300 assn standard single material response or cagec 73030 hs132 grade 4 mfr ref single material response |
| Surface Treatment: |
| Cadmium |
| |

NSN 5305-01-147-8314

Socket Head Cap Screw - Page 2 of 2



Surface Treatment Specification:

Cagec 73030 hs74 mfr ref single treatment response

Supplementary Features:

Inactive for new design use dwg 69582d or e

Thread Series Designator:

Unf

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A003b0