Socket Head Cap Screw - Page 1 of 2



AeroBase

View Online at https://aerobasegroup.com/nsn/5305-01-147-8725

3aThread Direction:Right-handThread Length:0.750 inchesFastener Length:Between 0.845 inches and 0.875 inchesHead Style:Flat chamferHead Diameter:Between 0.218 inches and 0.226 inchesHead Height:Between 0.134 inches and 0.138 inchesHole Diameter:Between 0.033 inches and 0.039 inchesHurenal Drive Style:HexagonThread Diameter:0.138 inchesHexagonChrash InchesHexagonHitches Flats:Between 0.109 inches and 0.111 inchesHole Quantity:2
Right-handThread Length:0.750 inchesFastener Length:Between 0.845 inches and 0.875 inchesHead Style:Flat chamferHead Diameter:Between 0.218 inches and 0.226 inchesHead Height:Between 0.134 inches and 0.138 inchesHole Diameter:Between 0.134 inches and 0.039 inchesInternal Drive Style:HexagonThread Diameter:0.138 inchesWidth Across Flats:Between 0.109 inches and 0.111 inchesHole Quantity:
Tread Length:0.750 inchesFastener Length:Between 0.845 inches and 0.875 inchesHead Style:Flat chamferHead Diameter:Between 0.218 inches and 0.226 inchesHead Height:Between 0.134 inches and 0.138 inchesHole Diameter:Between 0.134 inches and 0.138 inchesHorenal Drive Style:HexagonThread Diameter:0.138 inchesHexagonHexagonHole Diameter:0.138 inchesHexagonHole Diameter:0.138 inchesHexagonHole Diameter:0.138 inchesHole Diameter:0.139 inchesHole Diameter:0.139 inchesHole Diameter:Detween 0.109 inches and 0.111 inchesHole Quantity:
Tread Length:0.750 inchesFastener Length:Between 0.845 inches and 0.875 inchesHead Style:Flat chamferHead Diameter:Between 0.218 inches and 0.226 inchesHead Height:Between 0.134 inches and 0.138 inchesHole Diameter:Between 0.134 inches and 0.138 inchesHorenal Drive Style:HexagonThread Diameter:0.138 inchesHexagonHexagonHole Diameter:0.138 inchesHexagonHole Diameter:0.138 inchesHexagonHole Diameter:0.138 inchesHole Diameter:0.139 inchesHole Diameter:0.139 inchesHole Diameter:Detween 0.109 inches and 0.111 inchesHole Quantity:
0.750 inches Fastener Length: Between 0.845 inches and 0.875 inches Head Style: Flat chamfer Head Diameter: Between 0.218 inches and 0.226 inches Head Height: Between 0.134 inches and 0.226 inches Head Height: Between 0.134 inches and 0.138 inches Hole Diameter: Between 0.033 inches and 0.039 inches Hexagon Thread Diameter: 0.138 inches Width Across Flats: Between 0.109 inches and 0.111 inches Hole Quantity:
Between 0.845 inches and 0.875 inches Head Style: Flat chamfer Head Diameter: Between 0.218 inches and 0.226 inches Head Height: Between 0.134 inches and 0.128 inches Hole Diameter: Between 0.033 inches and 0.039 inches Hole Diameter: Hexagon Thread Diameter: 0.138 inches Width Across Flats: Between 0.109 inches and 0.111 inches
Between 0.845 inches and 0.875 inches Head Style: Flat chamfer Head Diameter: Between 0.218 inches and 0.226 inches Head Height: Between 0.134 inches and 0.128 inches Hole Diameter: Between 0.033 inches and 0.039 inches Hole Diameter: Hexagon Thread Diameter: 0.138 inches Width Across Flats: Between 0.109 inches and 0.111 inches
Flat chamferHead Diameter:Between 0.218 inches and 0.226 inchesHead Height:Between 0.134 inches and 0.138 inchesHole Diameter:Between 0.033 inches and 0.039 inchesInternal Drive Style:HexagonThread Diameter:0.138 inchesWidth Across Flats:Between 0.109 inches and 0.111 inchesHole Quantity:
Flat chamferHead Diameter:Between 0.218 inches and 0.226 inchesHead Height:Between 0.134 inches and 0.138 inchesHole Diameter:Between 0.033 inches and 0.039 inchesInternal Drive Style:HexagonThread Diameter:0.138 inchesWidth Across Flats:Between 0.109 inches and 0.111 inchesHole Quantity:
Between 0.218 inches and 0.226 inches Head Height: Between 0.134 inches and 0.138 inches Hole Diameter: Between 0.033 inches and 0.039 inches Internal Drive Style: Hexagon Thread Diameter: 0.138 inches Width Across Flats: Between 0.109 inches and 0.111 inches Hole Quantity:
Head Height:Between 0.134 inches and 0.138 inchesHole Diameter:Between 0.033 inches and 0.039 inchesInternal Drive Style:HexagonThread Diameter:0.138 inchesWidth Across Flats:Between 0.109 inches and 0.111 inchesHole Quantity:
Between 0.134 inches and 0.138 inches Hole Diameter: Between 0.033 inches and 0.039 inches Internal Drive Style: Hexagon Thread Diameter: 0.138 inches Width Across Flats: Between 0.109 inches and 0.111 inches Hole Quantity:
Between 0.134 inches and 0.138 inches Hole Diameter: Between 0.033 inches and 0.039 inches Internal Drive Style: Hexagon Thread Diameter: 0.138 inches Width Across Flats: Between 0.109 inches and 0.111 inches Hole Quantity:
Between 0.033 inches and 0.039 inches Internal Drive Style: Hexagon Thread Diameter: 0.138 inches Width Across Flats: Between 0.109 inches and 0.111 inches Hole Quantity:
Internal Drive Style: Hexagon Thread Diameter: 0.138 inches Width Across Flats: Between 0.109 inches and 0.111 inches Hole Quantity:
Hexagon Thread Diameter: 0.138 inches Width Across Flats: Between 0.109 inches and 0.111 inches Hole Quantity:
Hexagon Thread Diameter: 0.138 inches Width Across Flats: Between 0.109 inches and 0.111 inches Hole Quantity:
0.138 inches Width Across Flats: Between 0.109 inches and 0.111 inches Hole Quantity:
Width Across Flats: Between 0.109 inches and 0.111 inches Hole Quantity:
Between 0.109 inches and 0.111 inches Hole Quantity:
Hole Quantity:
2
Hole Type:
Drilled
Thready Qty Per Inch (tpi):
32
Min. Tensile Strength (psi):
160000 pounds per square inch
Hole Configuration Style:
Round internal hexagon
Material:
Iron alloy 660
Material Specification:
Ams 5731 assn standard single material response or ams 5737 assn standard single material response
Surface Treatment:
Passivate
Surface Treatment Specification:
Qq-p-35 federal specification single treatment response
Thread Series Designator:
Unrc

## NSN 5305-01-147-8725

Socket Head Cap Screw - Page 2 of 2



**Specification Data:** 

80205-nas1352 professional/industrial association standard

Shelf Life:

N/a

Unit Of Measure:

---

## Demilitarization:

No

Fiig:

A003b0