## NSN 5305-01-147-9766

Socket Head Cap Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-147-9766 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.387 inches and 0.500 inches **Fastener Length:** Between 0.470 inches and 0.500 inches **Head Style:** Flat chamfer **Head Diameter:** Between 0.303 inches and 0.312 inches **Head Height:** Between 0.185 inches and 0.190 inches **Internal Drive Style:** Hexagon **Thread Diameter:** 0.190 inches Width Across Flats: 0.156 inches Thready Qty Per Inch (tpi): 24 Min. Tensile Strength (psi): 180000 pounds per square inch **Hardness Rating:** 38.0 rockwell c and 45.0 rockwell c Minimum Yield Strength: 155000 pounds per square inch Material: Steel **Surface Treatment:** Zinc and chromate **Surface Treatment Specification:** Qq-z-325, type 2, cl 3 federal specification single treatment response **Thread Series Designator:** Unc **Specification Or Standard:** 6 type Shelf Life: N/a

**Unit Of Measure:** 

## NSN 5305-01-147-9766

Socket Head Cap Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0