NSN 5305-01-147-9775

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-147-9775

| Thread Class: |
|---|
| 3a |
| Thread Direction: |
| Right-hand |
| Thread Length: |
| Between 0.325 inches and 0.392 inches |
| Fastener Length: |
| Between 1.210 inches and 1.257 inches |
| Head Style: |
| Flat countersunk |
| Head Diameter: |
| Between 0.573 inches and 0.635 inches |
| Grip Diameter: |
| Between 0.3108 inches and 0.3117 inches |
| Internal Drive Style: |
| High-torque |
| Thread Diameter: |
| 0.312 inches |
| Grip Length: |
| Between 0.865 inches and 0.885 inches |
| Thready Qty Per Inch (tpi): |
| 24 |
| Min. Tensile Strength (psi): |
| 220000 pounds per square inch |
| Hardness Rating: |
| 46.0 rockwell c and 50.0 rockwell c |
| Countersink Angle: |
| Between 99.0 degrees and 101.0 degrees |
| Surface Finish: |
| 32.0 microinches grip |
| Product Name: |
| Navy special project |
| Material: |
| Steel comp h11 |
| Material Specification: |
| Ams6487 assn standard single material response |
| Surface Treatment: |
| Cadmium or cadmium and chromate |
| Surface Treatment Specification: |
| Nas672 assn standard 1st treatment response or mil-c-8837 ty2 cl2 military specification 2nd treatment response |
| Thread Series Designator: |

Unjf

NSN 5305-01-147-9775

Close Tolerance Screw - Page 2 of 2



| N/a | |
|-------------------|--|
| Unit Of Measure: | |
| | |
| Demilitarization: | |
| No | |
| Fiig: | |
| A003b0 | |

Mil-std (military Standard):

Shelf Life:

Mil-c-8837 spec.