NSN 5305-01-148-0238

Socket Head Cap Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-148-0238 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 0.451 inches and 0.514 inches **Fastener Length:** 0.625 inches **Head Style:** Flat countersunk **Head Diameter:** Between 0.311 inches and 0.359 inches **Internal Drive Style:** Hexagon **Thread Diameter:** 0.164 inches Width Across Flats: 0.094 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 80000 pounds per square inch Minimum Yield Strength: 40000 pounds per square inch **Countersink Angle:** Between 80.0 degrees and 82.0 degrees **Surface Finish:** 63.0 microinches threads Material: Nickel alloy 400 **Material Specification:** Qq-n-281 federal specification single material response **Surface Treatment:** Cadmium and chromate **Surface Treatment Specification:** Qq-p-416, ty2, cl3 federal specification single treatment response **Thread Series Designator:** Unc **Specification Or Standard:** 4 type

Shelf Life:

N/a

NSN 5305-01-148-0238

Socket Head Cap Screw - Page 2 of 2



			ure:	

--

Demilitarization:

No

Fiig:

A003b0