# NSN 5305-01-148-2651

Shoulder Screw - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5305-01-148-2651



#### **Thread Class:**

2a

**Thread Direction:** 

**Right-hand** 

### Thread Length:

0.250 inches

#### Fastener Length:

Between 0.750 inches and 0.752 inches

**Head Style:** 

Flat chamfer

#### Head Diameter:

0.375 inches

#### Head Height:

0.188 inches

#### Shoulder Diameter:

0.249 inches first shoulder and 0.250 inches first shoulder

#### Shoulder Length:

0.500 inches first shoulder and 0.502 inches first shoulder

#### Internal Drive Style:

Hexagon

#### **Thread Diameter:**

0.190 inches

#### Width Across Flats:

0.125 inches

#### Thready Qty Per Inch (tpi):

32

#### **Criticality Code Justification:**

Zzzy

#### Shoulder Shape:

Round first shoulder

#### Material:

Steel comp 303

#### Surface Treatment:

Chromium

#### **Special Test Features:**

Special quality control testing

#### Surface Treatment Specification:

Qq-c-320 class 2b federal specification single treatment response

## **Test Data Document:**

81349-mil-p-23199 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

## **Thread Series Designator:**

Unf

# NSN 5305-01-148-2651

Shoulder Screw - Page 2 of 2



### **Reference Number Differentiating Characteristics:**

As differentiated by material which must conform to ships parts control center special quality control provisions and certified free from

mercury contamination

Shelf Life:

N/a

## Unit Of Measure:

---

## Demilitarization:

No

Fiig:

A003b0