## NSN 5305-01-148-3682

Socket Head Cap Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-148-3682

Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
Between 4.766 inches and 5.000 inches
Fastener Length:
Between 4.920 inches and 5.000 inches
Head Style:
Flat chamfer
Head Diameter:
Between 0.735 inches and 0.750 inches
Head Height:
Between 0.492 inches and 0.500 inches
Hole Diameter:
0.062 inches
Internal Drive Style:
Hexagon
Thread Diameter:
0.500 inches
Width Across Flats:
0.375 inches
Hole Quantity:
4
Hole Type:
Drilled
Thready Qty Per Inch (tpi):
13
Min. Tensile Strength (psi):
170000 pounds per square inch
Hardness Rating:
38.0 rockwell c and 45.0 rockwell c
Minimum Yield Strength:
150000 pounds per square inch
Hole Configuration Style:
Round internal hexagon
Material:
Steel
Surface Treatment:
Zinc and chromate
Surface Treatment Specification:
Qq-z-325, type 2, cl 3 federal specification single treatment response

## NSN 5305-01-148-3682

Socket Head Cap Screw - Page 2 of 2



Inread Series Designator:
Unc
Specification Or Standard:
6 type
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A003b0