NSN 5305-01-148-5909



Socket Head Cap Screw - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5305-01-148-5909 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.260 inches and 0.387 inches **Fastener Length:** Between 0.470 inches and 0.500 inches **Head Style:** Flat countersunk **Head Diameter:** Between 0.359 inches and 0.411 inches **Locking Feature:** Patch threads or strip threads **Internal Drive Style:** Hexagon **Thread Diameter:** 0.190 inches Width Across Flats: 0.125 inches Thready Qty Per Inch (tpi): 24 Min. Tensile Strength (psi): 160000 pounds per square inch Hardness Rating: 36.0 rockwell c and 45.0 rockwell c **Countersink Angle:** Between 80.0 degrees and 84.0 degrees Material: Steel **Surface Treatment:** Cadmium and chromate **Surface Treatment Specification:** Qq-p-416, type 2, cl 3 federal specification single treatment response **Thread Series Designator:** Unc **Specification Or Standard:**

4 type Shelf Life: N/a **Unit Of Measure:**

NSN 5305-01-148-5909

Socket Head Cap Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0