NSN 5305-01-148-6234

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-148-6234 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 0.350 inches and 0.370 inches **Fastener Length:** Between 1.359 inches and 1.406 inches **Head Style:** Hexagon **Head Height:** Between 0.080 inches and 0.095 inches Width Between Flats: Between 0.241 inches and 0.250 inches **First Diameter From Head:** Between 0.097 inches and 0.102 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 1.009 inches and 1.036 inches **Internal Drive Style:** Cross recess type 1 **Thread Diameter:** 0.138 inches Thready Qty Per Inch (tpi): Min. Tensile Strength (psi): 125000 pounds per square inch Hardness Rating: 26.0 rockwell c and 32.0 rockwell c **Externally Relieved Body Diameter Quantity:** 1 Material: Steel comp 8630 or steel comp 4037 **Material Specification:** Mil-s-6050 military specification single material response **Surface Treatment:** Cadmium **Surface Treatment Specification:** Qq-p-416, type 2, class 3 federal specification single treatment response **Thread Series Designator:** Unc Shelf Life:

N/a

NSN 5305-01-148-6234

Externally Relieved Body Screw - Page 2 of 2



<i>l</i> leasure:

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-s-6050 spec.