## NSN 5305-01-148-6235

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-148-6235 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: 0.281 inches **Fastener Length:** 0.688 inches **Head Style:** Pan **Head Diameter:** Between 0.306 inches and 0.322 inches **Head Height:** Between 0.105 inches and 0.115 inches **First Diameter From Head:** 0.120 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: 0.407 inches **Internal Drive Style:** Cross recess type 1 **Thread Diameter:** 0.164 inches Thready Qty Per Inch (tpi): Min. Tensile Strength (psi): 1120 pounds per square inch **Externally Relieved Body Diameter Quantity:** Material: Steel **Material Specification:** Qq-s-763 federal specification single material response **Surface Treatment: Passivate Surface Treatment Specification:** Mil-f-14072 military specification single treatment response **Thread Series Designator:** Unc Shelf Life: N/a **Unit Of Measure:** 

## NSN 5305-01-148-6235

Externally Relieved Body Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-f-14072 spec.