## NSN 5305-01-148-9768

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-148-9768 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: 0.625 inches **Fastener Length:** 1.750 inches **Head Style:** Pan no. 2 **Head Diameter:** 1.000 inches **Head Height:** 0.312 inches **First Diameter From Head:** 0.375 inches **Second Diameter From Head:** 0.281 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: 0.250 inches Distance From Largest Bearing Surface Of Head To End Of Second Diameter: 1.125 inches **Internal Drive Style:** Slot **Thread Diameter:** 0.375 inches Thready Qty Per Inch (tpi): **Criticality Code Justification:** Zzzy **Externally Relieved Body Diameter Quantity: Special Features:** Straight knurl Material: Steel comp 303 **Special Test Features:** Special quality control testing

81349-mil-p-23199 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification

format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain

environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Test Data Document:** 

**Thread Series Designator:** 

Unc

## NSN 5305-01-148-9768

Externally Relieved Body Screw - Page 2 of 2



## **Reference Number Differentiating Characteristics:**

As differentiated by material which must confrom to ships parts control center special quality control provisions and certified free from mercury contamination

Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:

A003b0