NSN 5305-01-148-9768

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-148-9768 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: 0.625 inches **Fastener Length:** 1.750 inches **Head Style:** Pan no. 2 **Head Diameter:** 1.000 inches **Head Height:** 0.312 inches **First Diameter From Head:** 0.375 inches **Second Diameter From Head:** 0.281 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: 0.250 inches Distance From Largest Bearing Surface Of Head To End Of Second Diameter: 1.125 inches **Internal Drive Style:** Slot **Thread Diameter:** 0.375 inches Thready Qty Per Inch (tpi): **Criticality Code Justification:** Zzzy **Externally Relieved Body Diameter Quantity: Special Features:** Straight knurl Material: Steel comp 303 **Special Test Features:** Special quality control testing

81349-mil-p-23199 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification

format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain

environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Test Data Document:

Thread Series Designator:

Unc

NSN 5305-01-148-9768

Externally Relieved Body Screw - Page 2 of 2



Reference Number Differentiating Characteristics:

As differentiated by material which must confrom to ships parts control center special quality control provisions and certified free from mercury contamination

Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:

A003b0