## NSN 5305-01-148-9773

Machine Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-148-9773 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.469 inches and 0.562 inches **Fastener Length:** Between 0.531 inches and 0.562 inches **Head Style:** Flat chamfer **Head Diameter:** Between 0.306 inches and 0.313 inches **Head Height:** Between 0.103 inches and 0.118 inches **Internal Drive Style:** Torque set **Thread Diameter:** 0.190 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 160000 pounds per square inch **Hardness Rating:** Between 24.0 rockwell c and 35.0 rockwell c **Screw Material:** Iron alloy 660 **Screw Material Specification:** Ams 5737 assn standard single material response **Screw Surface Treatment: Passivate Screw Surface Treatment Specification:** Qq-p-35 federal specification single treatment response **Thread Series Designator:** Unjf **Specification Data:** 80205-nas1101 professional/industrial association standard Shelf Life: N/a **Unit Of Measure:** 

Demilitarization:

No

## NSN 5305-01-148-9773

Machine Screw - Page 2 of 2



Fiig:

A500d0