NSN 5305-01-149-1933

Socket Head Cap Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-149-1933 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.567 inches and 0.706 inches **Fastener Length:** 1.237 inches **Head Style:** Oval countersunk **Head Diameter:** Between 0.430 inches and 0.440 inches **Internal Drive Style:** Hexagon **Thread Diameter:** 0.250 inches Width Across Flats: Between 0.141 inches and 0.143 inches Thready Qty Per Inch (tpi): 28 **Countersink Angle:** 100.0 degrees **Special Features:** Furnished with one spring, thread to be double lead. Material: Steel comp 4140 or steel comp 8740 **Material Specification:** Mil-s-5626 military specification 1st material response or mil-s-6049 military specification 2nd material response **Surface Treatment:** Cadmium and chromate **Surface Treatment Specification:** Qq-p-416 type 2 class 2 federal specification single treatment response **Thread Series Designator:** Unf Shelf Life: N/a **Unit Of Measure: Demilitarization:**

No Fiig:

A003b0

NSN 5305-01-149-1933

Socket Head Cap Screw - Page 2 of 2



Mil-std (military Standard):

Mil-s-5626 spec.