## NSN 5305-01-149-1943

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-149-1943

Thr	ead Class:
3a	
Thr	ead Direction:
Rigi	it-hand
Thr	ead Length:
Betv	veen 1.338 inches and 1.388 inches
Fas	tener Length:
Betv	veen 1.973 inches and 2.003 inches
Hea	d Style:
Pan	no. 2
Hea	d Diameter:
Betv	veen 0.360 inches and 0.374 inches
Hea	d Height:
Betv	veen 0.115 inches and 0.125 inches
Grip	Diameter:
Betv	veen 0.1885 inches and 0.1895 inches
Inte	rnal Drive Style:
Hig	n-torque
Thr	ead Diameter:
0.19	0 inches
Grip	Dength:
Betv	veen 0.615 inches and 0.635 inches
Thr	eady Qty Per Inch (tpi):
32	
Min	Tensile Strength (psi):
160	000 pounds per square inch
Sur	ace Finish:
32.0	microinches threads
Mat	erial:
Iron	alloy 660
Mat	erial Specification:
Ams	5731 assn standard single material response or ams 5732 assn standard single material response or ams 5737 assn standard single
mat	erial response
Sur	ace Treatment:
Pas	sivate
Sur	ace Treatment Specification:
Qq-	p-35 federal specification single treatment response
Thr	ead Series Designator:
Unjf	
Spe	cification Data:
	05-nas1578 professional/industrial association standard
She	If Life:

N/a

## NSN 5305-01-149-1943

Close Tolerance Screw - Page 2 of 2

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A003b0

