
NSN 5305-01-149-3054

Socket Head Cap Screw - Page 1 of 2





Thread Class: 3a **Thread Direction: Right-hand Thread Length:** Between 0.232 inches and 0.312 inches Fastener Length: Between 0.282 inches and 0.312 inches **Head Style:** Flat chamfer **Head Diameter:** Between 0.176 inches and 0.183 inches **Head Height:** Between 0.108 inches and 0.112 inches Hole Diameter: Between 0.033 inches and 0.039 inches **Internal Drive Style:** Hexagon **Thread Diameter:** 0.112 inches Width Across Flats: Between 0.0937 inches and 0.0952 inches Hole Quantity: Hole Type: Drilled Thready Qty Per Inch (tpi): 40 Min. Tensile Strength (psi): 160000 pounds per square inch Hole Configuration Style: Round internal hexagon Material: Iron alloy 660 **Material Specification:** Ams5731 assn standard single material response or ams5737 assn standard single material response **Surface Treatment:** Passivate **Surface Treatment Specification:** Qq-p-35 federal specification single treatment response **Thread Series Designator:**

Unrc

2

NSN 5305-01-149-3054

Socket Head Cap Screw - Page 2 of 2



Specification Data:

80205-nas1352 professional/industrial association standard

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A003b0