## NSN 5305-01-149-7360

Shoulder Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-149-7360 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.363 inches and 0.398 inches **Fastener Length:** Between 1.048 inches and 1.078 inches **Head Style:** Flat chamfer **Head Diameter:** Between 0.365 inches and 0.385 inches **Head Height:** Between 0.052 inches and 0.072 inches **Shoulder Diameter:** 0.3105 inches first shoulder and 0.3110 inches first shoulder **Shoulder Length:** 0.630 inches first shoulder and 0.635 inches first shoulder **Internal Drive Style:** Torque **Thread Diameter:** 0.250 inches Thready Qty Per Inch (tpi): 20 Hardness Rating: 36.0 rockwell c and 42.0 rockwell c **Shoulder Shape:** Round first shoulder **Special Features:** Undercut under head 0.031 in. Wide Material: Steel comp 630 **Material Specification:** Aisi assn standard single material response **Surface Treatment: Passivate Surface Treatment Specification:** Qq-p-35 type 1 or type 2 or type 3 federal specification single treatment response **Thread Series Designator:** Unc Shelf Life:

N/a

## NSN 5305-01-149-7360

Shoulder Screw - Page 2 of 2



	1	:.	~	84				
ι	JN	IT	UΤ	IVI	ea	Sι	ire:	•

--

Demilitarization:

No

Fiig:

A003b0