## NSN 5305-01-150-1194

Machine Screw - Page 1 of 2

Between 0.469 inches and 0.500 inches

**Thread Class:** 

Right-hand **Thread Length:**0.464 inches

**Thread Direction:** 

Fastener Length:

**Head Style:** 

За



View Online at https://aerobasegroup.com/nsn/5305-01-150-1194

Flat countersunk
Head Diameter:
Between 0.126 inches and 0.162 inches
Locking Feature:
Strip
Internal Drive Style:
Cross recess type 1
Thread Diameter:
0.086 inches
Thready Qty Per Inch (tpi):
56
Min. Tensile Strength (psi):
160000 pounds per square inch
Countersink Angle:
Between 99.0 degrees and 101.0 degrees
Screw Material:
Iron alloy 660
Locking Feature Material:
Plastic polyamide
Screw Material Specification:
Ams 5737 assn standard single material response
Locking Feature Material Specification:
Mil-f-18240 military specification single material response
Screw Surface Treatment:
Passivate
Screw Surface Treatment Specification:
Qq-p-35 federal specification single treatment response
Bearing Surface Of Head Surface Finish:
32.0 microinches
Thread Surface Finish:
32.0 microinches
Thread Series Designator:
Unjc

## NSN 5305-01-150-1194

Machine Screw - Page 2 of 2



Speci	fication	Data
Opcoi	a	Duta

80205-nas1189 professional/industrial association standard

Shelf Life:

N/a

**Unit Of Measure:** 

\_\_

Demilitarization:

No

Fiig:

A500d0

Mil-std (military Standard):

Mil-f-18240 spec.