NSN 5305-01-150-8720

Assembled Washer Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-150-8720 **Thread Direction:** Right-hand Thread Length: Between 16.6 millimeters and 25.0 millimeters **Fastener Length:** 25.00 millimeters **Head Style:** Flat top elevator **Head Diameter:** Between 6.82 millimeters and 7.35 millimeters Washer Quantity: **Internal Drive Style:** Cross recess type ia **Thread Diameter:** 4.22 millimeters **Thread Pitch In Millimeters:** 4.2 **Countersink Angle:** Between 90.0 degrees and 92.0 degrees **Primary Washer Outside Diameter:** Between 8.95 millimeters and 9.45 millimeters **Primary Washer Style:** Flat **Primary Washer Material Thickness:** Between 0.35 millimeters and 0.50 millimeters Material: Steel fastener **Material Specification:** Sae assn standard all material responses primary washer **Surface Treatment:** Chromium **Surface Treatment Specification:** Gm 4251-m code 50 fscm 11862 mfr ref single treatment response **Thread Series Designator:** Shelf Life: N/a **Unit Of Measure:**

Demilitarization: No

NSN 5305-01-150-8720

Assembled Washer Screw - Page 2 of 2



Fiig:

A003b0