
Socket Head Cap Screw - Page 1 of 2





# **Thread Class:** 3a

**Thread Direction:** 

Right-hand

## Thread Length:

Between 0.073 inches and 0.141 inches

## Fastener Length:

Between 0.109 inches and 0.141 inches

#### **Head Style:**

Flat chamfer

Head Diameter:

Between 0.134 inches and 0.140 inches

#### **Head Height:**

Between 0.083 inches and 0.086 inches

#### Internal Drive Style:

Hexagon

#### Thread Diameter:

0.086 inches

#### Width Across Flats:

Between 0.078 inches and 0.079 inches

#### Thready Qty Per Inch (tpi):

56

#### Min. Tensile Strength (psi):

160000 pounds per square inch

#### **Product Name:**

Navy special project

#### Material:

Iron alloy 660

#### **Material Specification:**

Ams 5731 assn standard single material response or ams 5737 assn standard single material response

#### Surface Treatment:

Passivate

#### Surface Treatment Specification:

Qq-p-35 type 1 or type 2 or ty3 federal specification single treatment response

#### Thread Series Designator:

Unjc

# Shelf Life:

N/a

#### Unit Of Measure:

--

#### Demilitarization:

No

# NSN 5305-01-150-8725

Socket Head Cap Screw - Page 2 of 2

Fiig: A003b0

