NSN 5305-01-152-4694

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-152-4694 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 0.271 inches and 0.291 inches **Fastener Length:** Between 0.802 inches and 0.822 inches **Head Style:** Fillister **Head Diameter:** 0.401 inches **Head Height:** 0.222 inches **First Diameter From Head:** Between 0.175 inches and 0.185 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: 0.531 inches **Internal Drive Style:** Slot **Thread Diameter:** 0.250 inches Thready Qty Per Inch (tpi): **Criticality Code Justification:** Zzzy **Externally Relieved Body Diameter Quantity:** Material: Steel comp 305 **Surface Treatment:** Zinc and chromate **Special Test Features:** Special quality control testing **Surface Treatment Specification:** Qq-z-325, type 2 cl 3 federal specification single treatment response **Test Data Document:** 81349-mil-p-23199 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification

Thread Series Designator:

Unc

Reference Number Differentiating Characteristics:

As differentiated by material which must conform to ships parts control center special quality control provisions

environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain

NSN 5305-01-152-4694

Externally Relieved Body Screw - Page 2 of 2



_					
c	hο	JIF.		.ife:	
J			_	.II C.	

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0