NSN 5305-01-152-5623

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-152-5623 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.506 inches and 0.573 inches **Fastener Length:** Between 1.078 inches and 1.125 inches **Head Style:** Flat countersunk **Head Diameter:** Between 0.629 inches and 0.634 inches **Grip Diameter:** Between 0.3115 inches and 0.3120 inches **Internal Drive Style:** High-torque **Thread Diameter:** 0.312 inches **Grip Length:** Between 0.552 inches and 0.572 inches Thready Qty Per Inch (tpi): 24 Min. Tensile Strength (psi): 130000 pounds per square inch Hardness Rating: 24.0 rockwell c and 35.0 rockwell c Minimum Yield Strength: 85000 pounds per square inch **Countersink Angle:** 100.0 degrees **Surface Finish:** 32.0 microinches threads Material: Iron alloy 660 **Surface Treatment: Passivate Surface Treatment Specification:** Qq-p-35 federal specification single treatment response **Thread Series Designator:** Unf

Shelf Life:

N/a

NSN 5305-01-152-5623

Close Tolerance Screw - Page 2 of 2



ш	ın	10	<i>(</i>)+	Measure:	

--

Demilitarization:

No

Fiig:

A003b0