

View Online at <https://aerobasegroup.com/nsn/5305-01-153-0227>

Thread Direction:

Right-hand

Thread Length:

Between 17.0 millimeters and 18.5 millimeters

Fastener Length:

Between 109.5 millimeters and 111.0 millimeters

Head Style:

Hexagon extended washer

Head Height:

Between 9.1 millimeters and 10.9 millimeters

Width Between Flats:

Between 14.7 millimeters and 15.0 millimeters

Extended Washer Diameter:

21.5 millimeters

Extended Washer Thickness:

Between 1.8 millimeters and 3.6 millimeters

Thread Diameter:

10.0 millimeters

Min. Tensile Strength (psi):

900 megapascals

Thread Pitch In Millimeters:

1.5

External Thread Tolerance Class:

6g

Special Features:

Concave diamond knurled 16 impressions max. Equally spaced on 17.0 of grip

Material:

Steel

Material Specification:

Gm 500-m 9.8, fscm 11862 mfr ref single material response

Surface Treatment:

Zinc

Surface Treatment Specification:

Gm 4342-m code 20d48, fscm 11862 mfr ref single treatment response

Thread Series Designator:

M

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A003b0