## NSN 5305-01-153-0229

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-153-0229 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.476 inches and 0.526 inches **Fastener Length:** Between 1.174 inches and 1.204 inches **Head Style:** Flat countersunk **Head Diameter:** Between 0.578 inches and 0.634 inches **Grip Diameter:** Between 0.3110 inches and 0.3120 inches **Internal Drive Style:** High-torque **Thread Diameter:** 0.312 inches **Grip Length:** Between 0.678 inches and 0.698 inches Thready Qty Per Inch (tpi): 24 Min. Tensile Strength (psi): 160000 pounds per square inch Hardness Rating: 36.0 rockwell c and 40.0 rockwell c **Countersink Angle:** Between 99.0 degrees and 101.0 degrees **Surface Finish:** 32.0 microinches threads

**Product Name:** 

Navy special project

Material:

Steel comp e4340 or steel comp 4140 or steel comp 8740 or steel comp 6150 or steel comp 8735

**Surface Treatment:** 

Cadmium and chromate

**Surface Treatment Specification:** 

Qq-p-416, type 2 class 2 federal specification single treatment response

**Thread Series Designator:** 

Unjf

**Specification Data:** 

80205-nas1580 professional/industrial association standard

## NSN 5305-01-153-0229

Close Tolerance Screw - Page 2 of 2



_					
•	n	<b>0</b> 1	•	12	e:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A003b0