NSN 5305-01-154-2583

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-154-2583
Thread Class:
2a
Thread Direction:
Right-hand
Thread Length:
0.170 inches
Fastener Length:
Between 1.050 inches and 1.060 inches
Head Style:
Flat countersunk
Head Diameter:
Between 0.333 inches and 0.385 inches
First Diameter From Head:
Between 0.140 inches and 0.160 inches
Distance From Largest Bearing Surface Of Head To End Of First Diameter:
Between 0.797 inches and 0.807 inches
Internal Drive Style:
Cross recess type 1
Thread Diameter:
0.190 inches
Thready Qty Per Inch (tpi):
32
Min. Tensile Strength (psi):
80000 pounds per square inch
Countersink Angle:
Between 99.0 degrees and 101.0 degrees
Externally Relieved Body Diameter Quantity:
1
Material:
Steel comp 302 or steel comp 303 or steel comp 304
Surface Treatment:
Passivate
Surface Treatment Specification:
Qq-p-35 federal specification single treatment response
Thread Series Designator:
Unf
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:

No

NSN 5305-01-154-2583

Externally Relieved Body Screw - Page 2 of 2



Fiig:

A003b0