

View Online at <https://aerobasegroup.com/nsn/5305-01-154-5256>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 1.010 inches and 1.120 inches

**Fastener Length:**

Between 1.060 inches and 1.120 inches

**Head Style:**

Pan

**Head Diameter:**

Between 0.231 inches and 0.245 inches

**Head Height:**

Between 0.079 inches and 0.089 inches

**Internal Drive Style:**

Cross recess type 1

**Thread Diameter:**

0.125 inches

**Thready Qty Per Inch (tpi):**

40

**Criticality Code Justification:**

Zzzy

**Screw Material:**

Steel comp 302 or steel comp 302b or steel comp 303 or steel comp 303 plus x or steel comp 303se or steel comp 303cu or steel comp 303ma or steel comp 303pb or steel comp 304 or steel comp 304l

**Special Test Features:**

Special quality control testing

**Test Data Document:**

81349-mil-p-23199 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Thread Series Designator:**

Unc

**Reference Number Differentiating Characteristics:**

As differentiated by material which must conform to ships parts control center special quality control provisions

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A500d0