NSN 5305-01-154-5900

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-154-5900 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 0.240 inches and 0.260 inches **Fastener Length:** Between 0.672 inches and 0.704 inches **Head Style:** Fillister **Head Diameter:** Between 0.292 inches and 0.313 inches **Head Height:** Between 0.118 inches and 0.130 inches **First Diameter From Head:** Between 0.125 inches and 0.135 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.392 inches and 0.424 inches **Internal Drive Style:** Slot **Thread Diameter:** 0.190 inches Thready Qty Per Inch (tpi): **Externally Relieved Body Diameter Quantity:** 1 Material: Steel comp 303 or steel comp 303 plus x or steel comp 303ma or steel comp 203ez or steel comp 416se or steel comp 416 comp 416 plus x or steel comp 430f or steel comp 420fse **Material Specification:** Astm a581 assn standard all material responses **Surface Treatment: Passivate Surface Treatment Specification:** Qq-p-35 federal specification single treatment response **Thread Series Designator:** Unf Shelf Life: N/a **Unit Of Measure:**

No

Demilitarization:

NSN 5305-01-154-5900

Externally Relieved Body Screw - Page 2 of 2



Fiig:

A003b0