

View Online at <https://aerobasegroup.com/nsn/5305-01-154-5900>

**Thread Class:**

2a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.240 inches and 0.260 inches

**Fastener Length:**

Between 0.672 inches and 0.704 inches

**Head Style:**

Fillister

**Head Diameter:**

Between 0.292 inches and 0.313 inches

**Head Height:**

Between 0.118 inches and 0.130 inches

**First Diameter From Head:**

Between 0.125 inches and 0.135 inches

**Distance From Largest Bearing Surface Of Head To End Of First Diameter:**

Between 0.392 inches and 0.424 inches

**Internal Drive Style:**

Slot

**Thread Diameter:**

0.190 inches

**Thready Qty Per Inch (tpi):**

32

**Externally Relieved Body Diameter Quantity:**

1

**Material:**

Steel comp 303 or steel comp 303 plus x or steel comp 303ma or steel comp 203ez or steel comp 416se or steel comp 416 or steel comp 416 plus x or steel comp 430f or steel comp 420fse

**Material Specification:**

Astm a581 assn standard all material responses

**Surface Treatment:**

Passivate

**Surface Treatment Specification:**

Qq-p-35 federal specification single treatment response

**Thread Series Designator:**

Unf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A003b0