## NSN 5305-01-154-8481

Socket Head Cap Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-154-8481 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 0.288 inches and 0.380 inches **Fastener Length:** Between 0.350 inches and 0.380 inches **Head Style:** Flat chamfer **Head Diameter:** Between 0.303 inches and 0.312 inches **Head Height:** Between 0.185 inches and 0.190 inches **Internal Drive Style:** Hexagon **Thread Diameter:** 0.190 inches Width Across Flats: 0.156 inches Thready Qty Per Inch (tpi): 32 **Criticality Code Justification:** Zzzy **Special Features:** Item must comply with requirements of defense supply center philadelphiaproduction standard no. Ro0321 Material: Steel comp 302 or steel comp 302b or steel comp 303 or steel comp 303 plus x or steel comp 303se or steel comp 303cu or steel comp 303ma or steel comp 303pb or steel comp 304 or steel comp 304l **Special Test Features:** Special quality control testing **Test Data Document:** 81349-mil-p-23199 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). **Thread Series Designator:** Unc **Reference Number Differentiating Characteristics:** As differentiated by material which must conform to ships parts control center special quality control provisions Shelf Life: N/a

**Unit Of Measure:** 

Demilitarization:

## NSN 5305-01-154-8481

Socket Head Cap Screw - Page 2 of 2



Fiig:

A003b0