## NSN 5305-01-155-3394

Shoulder Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-155-3394

View Online at https://aerobasegroup.com/nsn/5305-01-155-3394
Thread Direction:
Right-hand
Thread Length:
9.5 millimeters
Fastener Length:
Between 21.50 millimeters and 21.75 millimeters
Head Style:
Flat chamfer
Head Diameter:
Between 9.78 millimeters and 10.00 millimeters
Head Height:
Between 4.32 millimeters and 4.50 millimeters
Shoulder Diameter:
5.982 millimeters first shoulder and 6.000 millimeters first shoulder
Shoulder Length:
12.00 millimeters first shoulder and 12.25 millimeters first shoulder
Internal Drive Style:
Hexagon
Thread Diameter:
5.0 millimeters
Width Across Flats:
3.0 millimeters
Min. Tensile Strength (psi):
1100 megapascals
Thread Pitch In Millimeters:
0.8
External Thread Tolerance Class:
6g
Shoulder Shape:
Round first shoulder
Material:
Steel property class 12.9
Surface Treatment:
Cadmium
Surface Treatment Specification:
Qq-p-416, type 1, class 1 federal specification single treatment response
Thread Series Designator:
Μ
Shelf Life:
N/a
Unit Of Measure:

---

## NSN 5305-01-155-3394

Shoulder Screw - Page 2 of 2

Demilitarization:

No

Fiig:

A003b0

