NSN 5305-01-155-5450

Shoulder Screw - Page 1 of 2



View Online at https://aerobasegroup.com/psn/5305-01-155-5450

View Online at https://aerobasegroup.com/nsn/5305-01-155-5450
Thread Class:
2a
Thread Direction:
Right-hand
Thread Length:
0.285 inches
Fastener Length:
0.615 inches
Head Style:
Fillister
Head Diameter:
Between 0.547 inches and 0.557 inches
Head Height:
0.187 inches
Shoulder Diameter:
0.281 inches all shoulders
Shoulder Length:
0.300 inches all shoulders
Internal Drive Style:
Slot
End Application:
Itank, full tracked, xm1; tank, full tracked, m1 w/improved armor; tank, full tracked, m1a1; sight gunners auxil, m1 abrams tank; gas, m1,
optical improvement program; gas, m1a1, oip; gunner's aux sight m1a1 abrams tank
Thread Diameter:
0.190 inches
Thready Qty Per Inch (tpi):
32
Shoulder Shape:
Round all shoulders
Special Features:
Identification plate type h, style3; attached to head w/adhesive backing 12273343; 0.375 in dia; 0.020 in thk; initials az on plate 0.125 in high
slot 0.062 in wd, 2 places
Material:
Stainless steel
Material Specification:
Astm a582, class 303, cond a assn standard single material response
Surface Treatment:
Passivate
Surface Treatment Specification:
Qq-p-35 federal specification single treatment response
Thread Series Designator:
Unf

N/a

Shelf Life:

NSN 5305-01-155-5450

Shoulder Screw - Page 2 of 2



		• •			
ш	ın	10	<i>(</i>)+	Measure:	

--

Demilitarization:

No

Fiig:

A003b0