

View Online at <https://aerobasegroup.com/nsn/5305-01-155-6113>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 1.280 inches and 1.790 inches

**Fastener Length:**

Between 2.900 inches and 3.000 inches

**Head Style:**

Hexagon

**Head Height:**

Between 0.348 inches and 0.371 inches

**Width Between Flats:**

Between 0.798 inches and 0.812 inches

**Thread Diameter:**

0.562 inches

**Thready Qty Per Inch (tpi):**

12

**Min. Tensile Strength (psi):**

120000 pounds per square inch

**Hardness Rating:**

25.0 rockwell c and 34.0 rockwell c

**Minimum Yield Strength:**

92000 pounds per square inch

**Material:**

Steel comp 1013 or steel comp 1015 or steel comp 1016 or steel comp 1017 or steel comp 1018 or steel comp 1019 or steel comp 1020 or steel comp 1021 or steel comp 1022 or steel comp 1023 or steel comp 1524 or steel comp 1025 or steel comp 1026 or steel comp 1527 or steel comp 1029 or steel comp 1030 or steel comp 1033 or steel comp 1034 or steel comp 1035 or steel comp 1536 or steel comp 1037 or steel comp 1038 or steel comp 1039 or steel comp 1040 or steel comp 1541

**Material Specification:**

Sae assn standard all material responses

**Surface Treatment:**

Phosphate

**Surface Treatment Specification:**

Gm 4435-m code a fscm 11862 mfr ref single treatment response

**Thread Series Designator:**

Unc

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0