100260

Externally Relieved Body Screw - Page 1 of 1

AeroBase Group

View Online at https://aerobasegroup.com/nsn/5305-01-155-9769

	······································
Thread Class:	
2a	
Thread Direction:	
Right-hand	
Thread Length:	
Between 0.267 inches and 0.287 inc	hes
Fastener Length:	
Between 0.719 inches and 0.750 inc	hes
Head Style:	
Pan	
Head Diameter:	
Between 0.306 inches and 0.322 inc	hes
Head Height:	
Between 0.105 inches and 0.115 inc	hes
First Diameter From Head:	
Between 0.114 inches and 0.124 inc	hes
Distance From Largest Bearing Su	urface Of Head To End Of First Diameter:
Between 0.432 inches and 0.483 inc	hes
Internal Drive Style:	
Cross recess type 1	
Thread Diameter:	
0.164 inches	
Thready Qty Per Inch (tpi):	
32	
Externally Relieved Body Diameter	r Quantity:
1	
Material:	
Steel comp 301 or steel comp 302 of	or steel comp 302b or steel comp 303 or steel comp 303se or steel comp 304 or steel comp 304l or
steel comp 305 or steel comp 308 c	or steel comp 309 or steel comp 309s or steel comp 310 or steel comp 310s or steel comp 314 or
steel comp 316 or steel comp 316	or steel comp 317 or steel comp 321 or steel comp 347 or steel comp 348 or steel comp 384 or stee
comp 385	
Surface Treatment:	
Passivate	
Surface Treatment Specification:	
Qq-p-35 federal specification single t	reatment response
Thread Series Designator:	
Unc	
Shelf Life:	
N/a	
Unit Of Measure:	
 Demilitarization:	
No	
Fiig:	
-	